



**STAINLESS STEEL
INDUSTRIAL CLEANING
TECHNOLOGY**



Start Up Instructions

1. Check the drain to make sure it's closed.
2. Open cabinet lid
3. Remove working tray and set aside
4. Add required amount of detergent
5. Fill with water to top of the chip basket
(located under the working tray)
6. Replace working tray
7. Power up the machine
8. Adjust thermostat to 117°



Optional Flo-Thru Brush

Removable Work Tray

Removable Work Tray



Main power button



Indicates pump is running

Indicates Heater is on

Low Water Indicator

Thermostat

The fill Line is the top of the chip basket

MAGIDO -High Pressure- Parts Washers



High Pressure Spray Wand

Lid supported by gas struts

Emergency Stop Button

Tank Drain

Adjustable Window
Clearing Manifold



Locking Cabinet With
Safety Stop

Tank Drain

Check Pre-Filter Daily

Foot pedal pump
switch

Machine Specifications



HP-25

Working Dimensions	W31.5"xL23"xH19.5"
--------------------	--------------------

Load Height From Floor	38.5"
------------------------	-------

Weight Capacity	350 lbs.
-----------------	----------

Fluid Capacity	40-Gallons
----------------	------------

Piston Drive Pump	2HP/3.6 GPM/870 PSI
-------------------	---------------------

Stainless Steel Heater	3kW
------------------------	-----